

Print date: 04.12.2020

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VME, Comp. A

UFI: N6X1-Y0MD-300P-HRM1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: MKT Metall-Kunststoff-Technik GmbH & Co. KG

Street: Auf dem Immel 2 Place: D-67685 Weilerbach

Telephone: +49(0)6374-91 16-0 Telefax: +49(0)6374-91 16-60

e-mail: info@mkt.de Internet: www.mkt.de

1.4. Emergency telephone +49 (0) 89-19240 (Giftnotruf München, German and English 24/7)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Causes skin irritation. Causes serious eve irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane;

Bisphenol-F-epichlorohydrin resin MM <= 700;

1,6-Bis(2,3-epoxypropoxy)hexane

Signal word: Warning

Pictograms:





GB - EN

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 2 of 13

Precautionary statements

P264 Wash hands thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

People who are allergic to epoxide should avoid the use of the product.

Use only outdoors or in a well-ventilated area.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
1675-54-3	2,2'-[(1-methylethylidene)bis(4,	1-phenyleneoxymethylene)]bisox	irane	25 - < 50 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Se	ens. 1, Aquatic Chronic 2; H315 F	1319 H317 H411	
9003-36-5	Bisphenol-F-epichlorohydrin re	sin MM <= 700		10 - < 20 %
	500-006-8		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aqua			
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane			10 - < 20 %
	618-939-5		01-2119463471-41	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412			
	Alkyl Ester (Ref.: 722 43/00/2012.0028, Germany)			1 - 10 %
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

Specific concentration limits and M-factors

CAS No	EC No	EC No Chemical name			
	Specific conce	Specific concentration limits and M-factors			
1675-54-3	216-823-5	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	25 - < 50 %		
	Skin Irrit. 2; H	315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100			

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 3 of 13

clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 4 of 13

Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: 5 - 35°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 5 of 13

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700			
Worker DNEL	_, acute	dermal	local	0,0083 mg/cm ²
Worker DNEL	., long-term	dermal	systemic	104,15 mg/kg bw/day
Worker DNEL	_, long-term	inhalation	systemic	29,39 mg/m ³
Consumer DN	NEL, long-term	dermal	systemic	62,5 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	systemic	8,7 mg/m ³
Consumer DN	NEL, long-term	oral	systemic	6,25 mg/kg bw/day
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane			
Worker DNEL	_, long-term	inhalation	systemic	10,57 mg/m ³
Worker DNEL	_, long-term	inhalation	local	0,44 mg/m ³
Worker DNEL	_, long-term	dermal	systemic	6,0 mg/kg bw/day
Worker DNEL	_, long-term	dermal	local	0,0226 mg/cm ²
Consumer DN	NEL, long-term	inhalation	systemic	5,29 mg/m ³
Consumer DN	NEL, long-term	inhalation	local	0,27 mg/m ³
Consumer DN	NEL, long-term	dermal	systemic	3,0 mg/kg bw/day
Consumer DN	NEL, long-term	dermal	local	0,0136 mg/cm ²
Consumer DN	NEL, acute	inhalation	systemic	5,29 mg/m ³
Consumer DN	NEL, acute	dermal	systemic	1,7 mg/kg bw/day
Consumer DN	NEL, acute	dermal	local	0,0136 mg/cm ²
Consumer DN	NEL, long-term	oral	systemic	1,5 mg/kg bw/day
Consumer DN	NEL, acute	oral	systemic	1,5 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmer	ntal compartment	Value
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700	
Freshwater		0,003 mg/l
Marine wate	er	0,0003 mg/l
Freshwater	sediment	0,294 mg/kg
Marine sedi	iment	0,0294 mg/kg
Secondary poisoning		0,0254 mg/l
Micro-orgar	nisms in sewage treatment plants (STP)	10 mg/l
Soil		0,237 mg/kg
933999-84-	9 1,6-Bis(2,3-epoxypropoxy)hexane	
Freshwater		0,0115 mg/l
Marine wate	er	0,00115 mg/l
Freshwater	sediment	0,283 mg/kg
Marine sedi	iment	0,283 mg/kg



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 6 of 13

Additional advice on limit values

This mixture contains quartz filler which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls







Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

Eye/face protection

Wear eye protection/face protection. Wear safety glasses.

Hand protection

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: 0,7 mm

DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: light beige
Odour: characteristic
Odour threshold: No data available

pH-Value: not determined

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Flash point:

not determined

not determined

not applicable

Flammability

Solid: not determined Gas: not applicable
Lower explosion limits: not determined Upper explosion limits: not determined



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 7 of 13

Auto-ignition temperature

Solid: not determined
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure:

Density (at 20 °C):

1,49 g/cm³

Water solubility:

The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

10.5. Incompatible materials

Keep away from: Oxidizing agent

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 8 of 13

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
9003-36-5	Bisphenol-F-epichloroh	ydrin resin	MM <= 700)		
	oral	LD50 mg/kg	> 2000	Rat		
	dermal	LD50 mg/kg	> 2000	Rat		
933999-84-9	1,6-Bis(2,3-epoxypropo	xy)hexane				
	oral	LD50 mg/kg	2190	Rat		OECD 401
	dermal	LD50 mg/kg	> 2000	Rat		OECD 402
	inhalation (4 h) vapour	LC50 mg/l	0,035	Rat		
	Alkyl Ester (Ref.: 722 4	3/00/2012.0	0028, Gern	nany)		
	oral	LD50 mg/kg	20700	Mouse		
	dermal	LD50 mg/kg	2000	Rabbit		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Contains epoxy constituents. May produce an allergic reaction. May cause an allergic skin reaction. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; Bisphenol-F-epichlorohydrin resin MM <= 700; 1,6-Bis(2,3-epoxypropoxy)hexane)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 9 of 13

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
9003-36-5	Bisphenol-F-epichlorohy	drin resin l	MM <= 700)			
	Acute fish toxicity	LC50 mg/l	2,54		Brachydanio rerio (zebra-fish)		
	Acute algae toxicity	ErC50	1,8 mg/l		Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 mg/l	2,55	48 h	Daphnia magna (Big water flea)		
933999-84-9	1,6-Bis(2,3-epoxypropox	xy)hexane					
	Acute fish toxicity	LC50	30 mg/l		Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50	47 mg/l		Daphnia magna (Big water flea)		

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700					
	OECD 301B	16 %	28			
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane					
	OECD 301D	71 %	28			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700	3,3
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane	0,822

BCF

CAS No	Chemical name	BCF	Species	Source
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane	3,57		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Print date: 04.12.2020

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 10 of 13

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Epoxy resin)

14.3. Transport hazard class(es): 9

14.4. Packing group:

Hazard label: 9



Classification code: M

Special Provisions: 274 335 375 601

Limited quantity: 5 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: -

Other applicable information (land transport)

No dangerous goods in packaging until 5 kg according special instruction 375 ADR/RID

Inland waterways transport (ADN)

14.1. UN number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

GB - EN

(Epoxy resin)

14.3. Transport hazard class(es): 9
14.4. Packing group:

Hazard label: 9



Classification code: M7



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 11 of 13

Special Provisions: 274 335 375 601

Limited quantity: 5 kg Excepted quantity: E1

Other applicable information (inland waterways transport)

No dangerous goods in packaging until 5kg according special instruction 375 ADN

Marine transport (IMDG)

14.1. UN number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9

Special Provisions: 274, 335, 966, 967, 969

Limited quantity: 5 kg
Excepted quantity: E1
EmS: F-A, S-F

Other applicable information (marine transport)

No dangerous goods in packaging until 5kg according 2.10.2.7 IMDG-Code

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Special Provisions: A97 A158 A179 A197

Limited quantity Passenger: 30 kg G Passenger LQ: Y956 Excepted quantity: E1

IATA-packing instructions - Passenger: 956
IATA-max. quantity - Passenger: 400 kg
IATA-packing instructions - Cargo: 956
IATA-max. quantity - Cargo: 400 kg

Other applicable information (air transport)

No dangerous goods in packaging until 5kg according A197 IATA-DGA

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

No information available.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 12 of 13

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU
E2 Hazardous to the Aquatic Environment

(SEVESO III):

Additional information

VOC content: 0,9 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 3,15.

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level

EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Dangerous Goods Code

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Chronic 2: Long-term aquatic hazard, Category 2

Aquatic Chronic 3: Long-term aquatic hazard, Category 3

Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1



Print date: 04.12.2020

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. A

Revision date: 29.10.2020 Page 13 of 13

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VME, Comp. B

UFI: 8S62-K0N2-R005-PVVG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: MKT Metall-Kunststoff-Technik GmbH & Co. KG

Street: Auf dem Immel 2 Place: D-67685 Weilerbach

Telephone: +49(0)6374-91 16-0 Telefax: +49(0)6374-91 16-60

e-mail: info@mkt.de Internet: www.mkt.de

1.4. Emergency telephone +49 (0) 89-19240 (Giftnotruf München, German and English 24/7)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1

Germ cell mutagenicity: Muta. 2 Reproductive toxicity: Repr. 1B

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements: Harmful if swallowed.

Causes severe skin burns and eye damage.

Causes serious eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects.

May damage fertility.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

3-aminomethyl-3,5,5-trimethylcyclohexylamine;

Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine);

m-Phenylenebis(methylamine);

Formaldehyde, oligomeric reaction products with 4,4'-isopropylidenediphenol and diethylenetriamine;

GB - EN

Print date: 04.12.2020

Diethylenetriamine;

Phenol; Bisphenol A

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 2 of 16

Pictograms:







Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.

H360F May damage fertility.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P310 Immediately call a POISON CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

2.3. Other hazards

Contains Amines. May produce an allergic reaction.

Use only outdoors or in a well-ventilated area.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 3 of 16

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	GHS Classification	•			
2855-13-2	3-aminomethyl-3,5,5-trimethylcy	clohexylamine		30 - < 40 %	
	220-666-8	612-067-00-9	01-2119514687-32		
	Acute Tox. 4, Acute Tox. 4, Skin H302 H314 H318 H317 H412	Corr. 1B, Eye Dam. 1, Skin Ser	ns. 1, Aquatic Chronic 3; H312		
1950616-36-0	Formaldehyde, oligomeric reacti	ion products with phenol and m-	phenylenebis(methylamine)	15 - < 25 %	
	701-207-5		01-2119966906-20		
	Skin Corr. 1C, Eye Dam. 1, Skin	Sens. 1B, Aquatic Chronic 3; F	1314 H318 H317 H412		
1477-55-0	m-Phenylenebis(methylamine)			15 - < 25 %	
	216-032-5		01-2119480150-50		
	Acute Tox. 4, Acute Tox. 4, Skin H302 H314 H318 H317 H412	Corr. 1B, Eye Dam. 1, Skin Ser	ns. 1B, Aquatic Chronic 3; H332		
77138-45-5	Formaldehyde, oligomeric reacti diethylenetriamine	ion products with 4,4´-isopropyli	denediphenol and	< 10,5 %	
	500-263-6		01-2120769506-44		
	Repr. 2, Skin Corr. 1B, Eye Dam	n. 1, Skin Sens. 1, STOT SE 3; I	H361f H314 H318 H317 H335		
90-72-2	2,4,6-Tris(dimethylaminomethyl)	phenol		5 - < 10 %	
	202-013-9		01-2119560597-27		
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H302 H315 H319				
100-51-6	Benzyl alcohol			5 - < 10 %	
	202-859-9	603-057-00-5	01-2119492630-38		
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319				
111-40-0	Diethylenetriamine			< 7 %	
	203-865-4	612-058-00-X	01-2119473793-27		
	Acute Tox. 2, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, STOT SE 3; H330 H312 H302 H314 H317 H335				
108-95-2	Phenol			1 - < 5 %	
	203-632-7	604-001-00-2	01-2119471329-32		
	Muta. 2, Acute Tox. 3, Acute Tox Chronic 2; H341 H331 H311 H3		Eye Dam. 1, STOT RE 2, Aquatic		
71074-89-0	Bis[(dimethylamino)methyl]phen	ol		1 - < 5 %	
	275-162-0				
	Skin Corr. 1B, Eye Dam. 1; H314 H318				
80-05-7	Bisphenol A			< 2 %	
	201-245-8	604-030-00-0	01-2119457856-23		
	Repr. 1B, Eye Dam. 1, Skin Sen H411	is. 1, STOT SE 3, Aquatic Chror	nic 2; H360F H318 H317 H335		

Full text of H and EUH statements: see section 16.

Specific concentration limits and M-factors

CAS No	EC No	Chemical name	Quantity	
	Specific conce	concentration limits and M-factors		
108-95-2	203-632-7	Phenol	1 - < 5 %	
	Skin Corr. 1B;	H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - < 3 Eye Irrit. 2; H319: >= 1 - < 3		



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 4 of 16

Further Information

SVHC list (Candidate List of Substances of Very High Concern for authorization): The product contains one of the listed substances: Bisphenol A

This mixture is place on the market in a form in which aerosol formation cannot occur during intended use and may only be used for applications in which aerosol formation is excluded. Workplace measurements to determine the exposure of users towards contained hazardous substances were carried out. Test reports show no need for the classification of the product as toxic by inhalation. The test reports are available. According to Article 6 of Regulation EC No. 1272/2008, classification and labeling as inhalation toxic is therefore not required.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eves

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After indestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

May damage fertility.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 5 of 16

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong, Organic peroxides Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature: 5 - 35°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 6 of 16

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-40-0	2,2'-Iminodi(ethylamine)	1	4.3		TWA (8 h)	WEL
80-05-7	Bisphenol A, inhalable dust	-	2		TWA (8 h)	WEL
108-95-2	Phenol	2	7.8		TWA (8 h)	WEL
		4	16		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
1950616-36- 0	Formaldehyde, oligomeric reaction products with phe	nol and m-phenylene	ebis(methylamine)				
Worker DNEL	., long-term	inhalation	systemic	0,02 mg/m ³			
Worker DNEL	., acute	inhalation	systemic	2,0 mg/m ³			
Worker DNEL	., long-term	inhalation	local	0,6 mg/m ³			
Worker DNEL	., acute	inhalation	local	6,0 mg/m ³			
Worker DNEL	., acute	dermal	local	2,8 mg/person/day			
Worker DNEL	., long-term	dermal	local	0,28 mg/person/day			
Worker DNEL	., acute	dermal	systemic	mg/kg bw/day			
1477-55-0	m-Phenylenebis(methylamine)						
Worker DNEL	., long-term	inhalation	systemic	1,2 mg/m ³			
Worker DNEL, long-term		inhalation	local	0,2 mg/m³			
Worker DNEL	., long-term	dermal	systemic	0,33 mg/kg bw/dav			

PNEC values

CAS No	Substance	
Environmenta	ll compartment	Value
1477-55-0	m-Phenylenebis(methylamine)	
Freshwater		0,094 mg/l
Marine water		0,009 mg/l
Freshwater sediment		0,43 mg/kg
Marine sediment		0,043 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,045 mg/kg
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	
Freshwater		0,084 mg/l
Marine water		0,0084 mg/l
Micro-organisms in sewage treatment plants (STP)		0,2 mg/l

Additional advice on limit values

This mixture contains quartz filler which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



Print date: 04.12.2020

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 7 of 16







Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke. Avoid contact during pregnancy and while nursing.

Eye/face protection

Wear eye protection/face protection. Wear safety glasses.

Hand protection

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: 0,7 mm

DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: black / red
Odour: characteristic
Odour threshold: No data available

pH-Value: not applicable

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Flash point:

not determined

not determined

not applicable

Flammability

Solid: not determined Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Auto-ignition temperature

Solid: not determined
Gas: not applicable

Decomposition temperature: not determined

GB - EN



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 8 of 16

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 1,07 g/cm³

Water solubility: The study does not need to be conducted

because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 9 of 16

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
2855-13-2	3-aminomethyl-3,5,5-ti	3-aminomethyl-3,5,5-trimethylcyclohexylamine							
	oral	LD50 mg/kg	1030	Rat					
	dermal	ATE mg/kg	1100						
1477-55-0	m-Phenylenebis(methy	ylamine)							
	oral	LD50 mg/kg	930	Rat					
	dermal	LD50 mg/kg	2000	Rabbit					
	inhalation (1 h) vapour			Rat					
	inhalation aerosol	ATE	1,5 mg/l						
90-72-2	2,4,6-Tris(dimethylami	nomethyl)p	henol						
	oral	LD50 mg/kg	2169	Rat					
	dermal	LD50 mg/kg	1280	Rat					
100-51-6	Benzyl alcohol								
	oral	LD50 mg/kg	1230	Rat					
	inhalation vapour	ATE	11 mg/l						
	inhalation aerosol	ATE	1,5 mg/l						
111-40-0	Diethylenetriamine								
	oral	LD50 mg/kg	1080	Rat					
	dermal	LD50 mg/kg	1054	Rabbit					
	inhalation vapour	ATE	0,5 mg/l						
	inhalation aerosol	ATE	0,05 mg/l						
108-95-2	Phenol								
	oral	LD50 mg/kg	650	Rat		OECD 401			
	dermal	LD50 mg/kg	630	Rabbit					
	inhalation vapour	ATE	3 mg/l						
	inhalation aerosol	LC50	0,9 mg/l	8 h Rat					
80-05-7	Bisphenol A								
	oral	LD50 mg/kg	3250	Rat					
	dermal	LD50 mg/kg	3000	Rabbit					

Irritation and corrosivity
Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 10 of 16

May cause an allergic skin reaction. (3-aminomethyl-3,5,5-trimethylcyclohexylamine; Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine); m-Phenylenebis(methylamine); Formaldehyde, oligomeric reaction products with 4,4´-isopropylidenediphenol and diethylenetriamine; Diethylenetriamine; Bisphenol A)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Phenol)

May damage fertility. (Bisphenol A)

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

This mixture is place on the market in a form in which aerosol formation cannot occur during intended use and may only be used for applications in which aerosol formation is excluded. Workplace measurements to determine the exposure of users towards contained hazardous substances were carried out. Test reports show no need for the classification of the product as toxic by inhalation. The test reports are available. According to Article 6 of Regulation EC No. 1272/2008, classification and labeling as inhalation toxic is therefore not required.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 11 of 16

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
1477-55-0	m-Phenylenebis(methylamine)						
	Acute fish toxicity	LC50 mg/l	87,6	96 h	Oryzias latipes (Ricefish)		OECD 203
	Acute algae toxicity	ErC50 mg/l	32,1	72 h	Selenastrum capricornutum		OECD 201
	Acute crustacea toxicity	EC50 mg/l	15,2	48 h	Daphnia magna (Big water flea)		OECD 202
	Crustacea toxicity	NOEC	4,7 mg/l	21 d	Daphnia magna (Big water flea)		OECD 211
90-72-2	2,4,6-Tris(dimethylamin	omethyl)pl	nenol				
	Acute fish toxicity	LC50	175 mg/l	96 h	Cyprinus carpio (Common Carp)		
	Acute algae toxicity	ErC50	84 mg/l	72 h	Desmodesmus subspicatus		OECD 201
	Algae toxicity	NOEC mg/l	6,25	3 d			
111-40-0	Diethylenetriamine						
	Acute fish toxicity	LC50	430 mg/l	96 h	Leuciscus idus		
	Acute algae toxicity	ErC50 mg/l	1164	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 mg/l	53,5	48 h	Daphnia magna		
108-95-2	Phenol						
	Acute fish toxicity	LC50	8,9 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	61,1	96 h			
	Acute crustacea toxicity	EC50	3,1 mg/l	48 h	Daphnia magna (Big water flea)		
	Crustacea toxicity	NOEC mg/l	0,16	16 d	Daphnia magna (Big water flea)		
80-05-7	Bisphenol A						
	Acute fish toxicity	LC50	4,6 mg/l		Pimephales promelas		
	Acute algae toxicity	ErC50 mg/l	2,73	96 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 mg/l	10,2	48 h	Daphnia magna		

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
80-05-7	Bisphenol A			
	OECD 301F	74,7 - 81,4	28	

12.3. Bioaccumulative potential

The product has not been tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 12 of 16

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	1,9
1477-55-0	m-Phenylenebis(methylamine)	0,18
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	0,219
100-51-6	Benzyl alcohol	1,05
111-40-0	Diethylenetriamine	-5,58
108-95-2	Phenol	1,5
80-05-7	Bisphenol A	3,4

BCF

CAS No	Chemical name	BCF	Species	Source
1477-55-0	m-Phenylenebis(methylamine)	2,69		
108-95-2	Phenol	17,5		
80-05-7	Bisphenol A	73		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

SECTION 14: Transport information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 13 of 16

Land transport (ADR/RID)

14.1. UN number: UN 3259

14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Classification code: C8
Special Provisions: 274
Limited quantity: 1 kg
Excepted quantity: E2
Transport category: 3
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 3259

14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Classification code: C8
Special Provisions: 274
Limited quantity: 1 kg
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 3259

14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Special Provisions: 274
Limited quantity: 1 kg
Excepted quantity: E2
EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3259

14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))

GB - EN

Print date: 04.12.2020

14.3. Transport hazard class(es): 8
14.4. Packing group: |



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 14 of 16

Hazard label: 8

8

Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3 A803

5 kg

Y844

Excepted quantity:

E2

IATA-packing instructions - Passenger:859IATA-max. quantity - Passenger:15 kgIATA-packing instructions - Cargo:863IATA-max. quantity - Cargo:50 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

Bisphenol A

Restrictions on use (REACH, annex XVII):

Entry 3: 3-aminomethyl-3,5,5-trimethylcyclohexylamine; 2,4,6-Tris(dimethylaminomethyl)phenol; Benzyl

alcohol; Diethylenetriamine Entry 66: Bisphenol A

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

Additional information

VOC content: 28,7 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 15.

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B

Revision date: 29.10.2020 Page 15 of 16

Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Dangerous Goods Code

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound Acute Tox. 2: Acute toxicity, Category 2 Acute Tox. 3: Acute toxicity, Category 3

Acute Tox. 4: Acute toxicity, Category 4

Aquatic Chronic 3: Long-term aquatic hazard, Category 3 Eye Dam. 1: Serious eye damage/eye irritation, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Repr. 1B: Reproductive toxicity, Category 1B Skin Sens. 1: Skin sensitilization, Category 1 Skin Sens. 1B: Skin sensitilization, Category 1B

STOT RE 2: Specific target organ toxicity (repeated exposure), Category 2 STOT SE 3: Specific target organ toxicity (single exposure), Category 3

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Repr. 1B; H360F	Calculation method
Aquatic Chronic 3; H412	Calculation method

GB - EN

Print date: 04.12.2020

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

VME, Comp. B					
Revision date: 29.10.2020		Page 16 of 16			
H330	Fatal if inhaled.				
H331 H332	Toxic if inhaled. Harmful if inhaled.				
H335 H341	May cause respiratory irritation. Suspected of causing genetic defects.				
H360F	May damage fertility.				
H361f H373	Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.				
H411	Toxic to aquatic life with long lasting effects.				
H412	Harmful to aquatic life with long lasting effects.				

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)